

DURALIFT

ELEVATED WORK PLATFORM HIRE

SPECIFICATION SHEET

LIFTPOD

FS80



SPECIFICATIONS

MEASUREMENTS

Platform Height	2.32 m
Working Height	4.32 m
Clearance Height	2.97 m
Assembled Machine Width	1.04 m
Assembled Machine Length	1.31 m
Machine Capacity	150 kg

PRODUCTIVITY

Wheel Diameter	200 mm
Wheel Material	Non-Marking Polyurethane
Max Wheel Bearing Load	100 kg
Max Wheel Bearing Pressure	100 psi
Rated Incline and Surface	Firm Level Surface
Leveling Front to Back	±1°
Leveling Side to Side	±0°
Lift Up Time	20-27 s
Lift Down Time	17-22 s

POWER

Up Down Cycles/Charge	20 lb 20 Cycles
Duty Cycle @ Rated Capacity	4 Cycles/15 min
Battery Cell Type	NiMh
Battery Capacity	4.5 Ah
Battery Voltage	28.8V
Power Pack Voltage	28V

Drive Options

Cordless Drill	Minimum 18V Drill not Included
Power Pack	28V, 4.5 Ah Optional Accessory

WEIGHT

Base Gross Weight	26 kg
Platform Gross Weight	15 kg
Mast Gross Weight	22 kg
Power Pack Gross Weight	8 kg
Machine Assembled Weight	63 kg



www.duralift.com.au



1300 580 580